



Model C-460SS

A multifunction unit for solution and blanket warming with independent temperature control for two separate chambers. Full stainless steel construction with stainless steel shelves. PID controller with timer function. The upper chamber is for blanket warming (35°C to 60°C). The lower chamber is for solution warming (35°C to 50°C).

Applications

Versatile and compact two-in-one unit warmer designed for use in nurseries, emergency departments, operation and recovery rooms.

Features

- Push button digital operation
- Large dual digital displays
- Displays actual temperature and set temperature at all times
- Uniform heating
- Fully insulated on all side walls
- Audible and visual over-temperature alarm
- Tall free-standing model
- Glass or stainless steel door(s)



Specifications

Model	C-460SS
Type	Floor-standing, double-door
Capacity	400 litres
Preset temperature	42°C
Working temperature range	35°C - 60°C for blanket warming cabinet (upper chamber) 35°C - 50°C for solution warming cabinet (lower chamber)
Safety devices	Built-in thermostat and ELCB. Fitted with temperature alarm to avoid overheating.
No. of shelves supplied	4 units (2 x 2)
Shelf material	Stainless steel
Shelf dimensions (mm)	525W x 410D x 15H (upper chamber shelf) 485W x 425D x 15H (lower chamber shelf)
Interior dimensions (mm)	540W x 460D x 800H (upper chamber) 540W x 480D x 800H (lower chamber)
Exterior dimensions (mm)	800W x 640D x 1915H
Power consumption	1000 watt x 2
Electrical	220 - 240 VAC, 50Hz, 4.6A
Weight	123 kg

All specifications are subject to change without prior notice.